

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000487

International filing date: 11 February 2005 (11.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0403335.3  
Filing date: 14 February 2004 (14.02.2004)

Date of receipt at the International Bureau: 18 April 2005 (18.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT/4B2005/000487



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


*William Morell*

Dated 4 April 2005



# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference

6/LC/P13221.GB

2. Patent application number  
(The Patent Office will fill in this part)

0403335.3

16FEB04 EB73526-4 D02915  
P01/7700 0.00-0403335.3 14FEB 2004

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Barry Peter Liversidge  
The Wick  
Wick Road  
Langham  
Colchester  
Essex CO4 5PE

Patents ADP number (if you know it)

77429001

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

MEDICAL INJECTOR HANDLING DEVICE

5. Name of your agent (if you have one)

Sanderson & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including postcode)

34 East Stockwell Street  
Colchester  
Essex  
CO1 1ST

Patents ADP number (if you know it)

1446001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

No

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 17

Claim(s) 5

Abstract -

Drawing(s) 6 + 6 *gm*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (Please specify)

11. Sanderson & Co.  
Agents for the applicant

I/We request the grant of a patent on the basis of this application.

Signature *[Signature]* Date 13th February 2004

12. Name and daytime telephone number of person to contact in the United Kingdom Francis C. Gillam - 01206 571187

## Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

DUPLICATE

- 1 -

## MEDICAL INJECTOR HANDLING DEVICE

This invention relates to a handling device for use with a medical injector having a cylindrical body provided with a boss at the forward end thereof for supporting a forwardly projecting needle furnished with a protective sheath.

Throughout this specification, the terms *forward* and *forwardly* in relation to  
5 an injector refer to the end of the injector at which the needle is mounted and the direction towards that end. Conversely, the terms *rearward* and *rearwardly* refer to the end of the injector opposed to the forward end and the direction away from the forward end thereof.

A drug in the form of a liquid may be administered (other than orally) to a  
10 human or animal body by means of an injector having a hollow needle in conjunction with a source of the required liquid drug. For example, the hollow needle may be associated with a small-volume syringe holding the liquid drug, the needle being used to penetrate the body at an injection site, at which the drug is to be received.

15 In recent years, there has been a trend towards self-administered drug delivery systems. Following on from advances in drug technology, it is now possible to treat conditions which previously may not have been treatable or only treatable with difficulty, though with these advances it often is necessary to deliver the appropriate drugs at frequent and regular intervals. By facilitating self-  
20 administration, this eases the burden on the medical services, as well as on a patient who may perform the required drug delivery injection wherever that person

happens to be, without needing to seek out the services of medically-qualified personnel.

A well-known and widely documented problem with needle-based drug delivery systems is the risk of so-called needle-stick injuries, where a person  
5 accidentally and inadvertently becomes injured by a needle. Before the needle has been used to perform an injection, this usually is of little consequence, but once the needle has been used, it may be a very much more serious matter. As such, there has been extensive research into and development of injection devices adapted to minimise the risk of needle-stick injuries.

10 Many people who are old or infirm might be suitable for treatment with self-administered injections, but are unable to perform the required safe operating procedures to minimise the risk of needle-stick injuries, either when preparing an injection device for administration of a drug, or subsequently when clearing-up after performing an injection and disposing of the used equipment. The present  
15 invention has been developed in an attempt to address these problems, particularly (but not exclusively) to facilitate the use of injection systems for the self-administration of drugs.

According to one aspect of this invention, there is provided a handling device for use with a medical injector having a cylindrical body provided with a  
20 boss at the forward end thereof supporting a forwardly-projecting needle furnished with a protective sheath, which device comprises:

- a carrier having an outer cylindrical wall and co-axial therewith an inner tube which is a close sliding fit over the protective sheath of a needle;

— a cylindrical sleeve slidably mounted within the outer cylindrical wall of the carrier, the rear end of the sleeve being adapted to receive the cylindrical body of the injector;

5 — a bushing slidably located within the cylindrical sleeve, which bushing is retained within the sleeve and defines a bore for receiving the boss at the forward end of the injector body;

— spring means urging the bushing towards the rear end of the sleeve; and

— a plug slidably mounted on the carrier and projectable from the forward end thereof, the forward end of the sheath of a received injector engaging the plug;

10 whereby in use the device may be fitted to the forward end of an injector by receiving the injector cylindrical body in the sleeve and the boss in the bore of the bushing, the sheath then coupling to the inner tube of the carrier and the forward end of the sheath engaging the plug and pushing the plug forwardly with respect to the carrier to project therefrom, and on subsequent withdrawal of the carrier from  
15 the injector, the bushing and sleeve remain on the injector and the sheath remains within the carrier with the plug projecting from the forward end thereof.

According to a further aspect of this invention, there is provided the combination of a handling device of this invention as described above, together with a medical injector having a cylindrical body provided with a boss at the forward  
20 end thereof for supporting a forwardly-projecting needle furnished with a protective a sheath, wherein the boss is receivable in the bore of the bushing, the sleeve is slidably rearwardly over the cylindrical body of the injector, and the sheath is connectable to the inner tube of the carrier.



According to yet another, and closely related, aspect of this invention, there is provided a method of using a handling device of this invention as described above, together with a medical injector having a cylindrical body provided with an externally-threaded boss at the forward end thereof for supporting a needle having  
5 an internally-threaded hub engageable with the threads of the boss and a needle sheath surrounding and protecting the needle. This method comprises the steps of:

- threading the hub of a needle on to the boss of the injector;

- pushing the carrier on to the forward end of the injector so that the injector  
10 body is slidably received in the cylindrical sleeve, the boss carrying the needle hub is received in the bore of the bushing, the sheath is coupled to the inner tube, and the sheath engages the plug and pushes the plug forwardly to project from the carrier;

- pulling the carrier away from the cylindrical body of the injector with the  
15 sheath retained within the inner tube, the sleeve remaining on the injector body and the bushing remaining on the needle hub and boss, with the sleeve being urged forwardly by the spring to protect the needle;

and following the performance of an injection, during which the sleeve slides rearwardly over the injector body against the action of the spring to expose the  
20 needle as required:

- pushing the carrier once more on to the forward end of the injector so receiving the sleeve into the carrier and refitting the sheath on to the needle;

– rotating the carrier to unthread the needle hub from the boss and freeing the carrier from the injector body with the needle and sheath carried therewithin; and

– pressing the projecting plug back into the carrier, so driving the sheathed  
5 needle out of the handling device.

It will be appreciated that the handling device of this invention allows the handling of a hollow injection needle in a safe manner, so minimising the risk of a needle-stick injury, either before or after the performance of an injection procedure, by maximising the guarding of the needle tip. The device is fitted to an injector  
10 while the needle thereof still carries its protective sheath, and then on removing the carrier of the device from the injector, the needle is unsheathed. The cylindrical sleeve remains with the injector, surrounding and so shielding the needle from accidental contact which otherwise could damage the needle tip, leaving aside the risk of a needle-stick injury. On performing the injection, the cylindrical sleeve  
15 slides axially rearwardly with respect to the injector to expose the needle, the sleeve sliding back again under its spring loading to protect the needle, on withdrawing the needle from the injection site.

The fitting of the device to the injector as described above causes the plug, which is slidably mounted on the carrier, to be projected forwardly by the sheath.  
20 Then, on removing the carrier, the projecting plug indicates that the carrier contains the sheath and thus shows that the injector is ready to perform an injection.

The sheath may couple to the inner tube upon fully entering that tube, by being a light frictional fit within the tube. Typically, the sheath tapers slightly

towards its free end so that it may easily enter a parallel bore defined by the inner tube, but then become gripped by the tube as the carrier is fully fitted to the injector. In an alternative arrangement, and depending upon the configuration of the sheath, a positive mechanical connection may be made between the sheath  
5 and the inner tube.

In a preferred aspect, following completion of the injection, the carrier may be refitted to the sleeve, so re-sheathing the needle. The entire device may then be removed from the injector in such a way that the sheathed needle remains within the device and so the sheathed needle is also removed from the injector,  
10 ready for disposal. For example, in the case of a needle having a hub which is threaded to the injector (as is usually the case for a self-administration injector), by turning the device in an unscrewing sense, the needle will be released from the injector with the device. Once removed from the injector, the carrier may be supported and on depressing the plug back thereinto, the sheathed needle will be  
15 driven out of the device, ready for disposal. For instance, the carrier containing the needle could be placed on a sharps container over the opening therein and the sheathed needle may then be discharged directly into the container. Alternatively, the device could be placed on a suitable surface such as a table-top and the plug depressed; the needle will quite safely be deposited on that surface for subsequent  
20 disposal, in view of the presence of the sheath on the needle.

In a preferred form of the invention, the carrier has an inner cylindrical wall connected at the forward end of the carrier to the outer cylindrical wall, the inner tube being connected to the rear end of the inner cylindrical wall. The cylindrical

sleeve may thus be slidable within the annular space between the inner and outer cylindrical walls of the carrier, and the plug being slidably supported within the inner cylindrical wall.

Preferably, the plug is a sufficient light frictional fit within the cylindrical wall  
5 to restrain movement of the plug with respect to the carrier, at least under the influence of gravity, so that no false indication will be given that the needle is still sheathed when in fact the sheath has been removed and is located within the carrier. Further, the plug may have a highly visible colour to ensure it gives an adequate warning of the fact a needle has been unsheathed.

10 The rear end of the sleeve is advantageously internally profiled to permit the bushing to be pushed into the sleeve, whereafter the bushing is retained within the sleeve. For example, radially inwardly-directed nibs or an annular internal rib may be provided on the sleeve and with which the bushing is engageable.

Many injectors intended for the self-administration of drugs are in the form of  
15 a so-called pen injector, having an elongate cylindrical outer body with a boss for a needle hub at a forward end of the body and a mechanism at the rear end of the body, permitting pre-selection of a required dose and then operable to dispense that dose. A handling device of this invention for use with such a pen injector may have a cylindrical sleeve of a sufficient length to enclose the greater part of the  
20 length of the pen injector body, when the carrier is fitted to the injector, but still permitting access to the mechanism at the rear end of the injector body. Then, on performing the injection, the sleeve may be gripped in the fist of a user, in the same way as a user would grip the body of the injector if being used without the

handling device of this invention. Once held in this way, the injector may be used in much the same way as would be a pen injector.

By having an elongate sleeve as just described, there follows the advantage that the forward end of the sleeve may be offered to the injection site at the required angle (and usually substantially perpendicularly), whereafter the pre-set  
5 mechanism at the rear end of the injector body may be depressed by a finger or thumb of the user. The initial pressure on that mechanism serves to move the entire injector forwardly within the sleeve, against the action of the spring acting between the bushing and the sleeve, so achieving needle penetration at the  
10 injection site. Continued pressure on the mechanism then dispenses the drug through the needle into the injection site. In this way, an injection may be performed in one simple and continuous action, rather than the user having to perform a first step of inserting the needle into the injection site and then a second and quite separate step of actuating the dispensing mechanism. Further, the  
15 needle remains shielded from the direct view of a patient, so assisting with the well-recognised aversion to needles suffered by many people.

By way of example only, two specific embodiments of handling device for use with a medical injector will now be described in detail, reference being made to the accompanying drawings, in which:

20 Figure 1 shows a second embodiment of handling device of this invention in association with an injector, the handling device having a relatively short outer sleeve, wherein Figures 1A to 1F are axial sections through the handling device

and a part of the injector showing the successive steps of the use of the injector and handling device to perform an injection; and

Figure 2 shows a handling device in association with a pen injector intended for the self-administration of a drug, wherein

5        Figure 2A shows the pen injector with the handling device fitted thereto, but before a disposable needle has been mounted on the injector;

Figure 2B is a partial sectional view of the assembly of Figure 2A;

Figures 2C to 2J show successive steps of the use of the injector and handling device to perform an injection.

10        *Note: the letter I is not used in the figure numbering, to avoid confusion with the numeral 1.*

Referring initially to Figures 1A to 1F, there is shown a first embodiment of handling device 10 for use with an injector 11. The injector comprises a cylindrical body 12 having an externally-threaded boss 13 at its forward end and adapted for  
15        the connection thereto of a needle 14 having an internally screw-threaded hub 15. A plunger (not shown) and including a piston (also not shown) at its forward end is slidably mounted within the body 12, to permit filling of the injector with a liquid medicament (drug) and then the dispensing of that medicament through an attached needle. Alternatively, a vial of the medicament and having an integral  
20        piston may be located within the body 12, the vial having a pierceable membrane at its forward end for penetration by the rear end of an attached needle.

As shown in Figures 1A and 1B, the needle is carried in a stub 16 forming a part of the hub 15, and a sheath 17 is fitted over the needle, that sheath being

engaged with the stub 16. The sheath is formed of a substantially rigid plastics material and has a rear flange 18 engaged with the needle hub 15. As such, the sheath will protect the needle against accidental contact during fitting of the needle to the injector 11 by threading the hub 15 on to the boss 13, the sheath being  
5 restrained against lateral movement with respect to the needle by virtue of the flange 18.

The handling device 10 has a carrier 20 defining an outer cylindrical wall 21 and an inner cylindrical wall 22 connected to the outer cylindrical wall at the forward end of the carrier by a further wall 23. Slidably mounted within the carrier,  
10 adjacent the outer cylindrical wall, is a cylindrical sleeve 24 internally profiled to permit the cylindrical body 12 of the injector to slide freely therewithin. The bore of the cylindrical sleeve 24 slidably carries a bushing 25 having an outer wall 26 which runs on the internal surface of the cylindrical sleeve, and an inner wall 27 adapted to receive the hub of a needle fitted to the injector. The rear end portion of  
15 the cylindrical sleeve 24 has an internal inwardly-projecting annular rib 28 over which the bushing may be bumped when fitting the bushing to the sleeve, but then serves to retain the bushing within the sleeve 24. A helical compression spring 29 is disposed within the sleeve 24 and acts between a forward flange 30 of the sleeve and the bushing 25, to urge the bushing towards the rear of the sleeve.

20 The rear end of the inner cylindrical wall 22 has an internally directed flange 32 supporting an inner tube 33 projecting forwardly from that flange. The bore of the tube is dimensioned so as to be able to receive the sheath 17 protecting the

needle, but to be a friction fit over the rear part of that sheath, thereby to grip the sheath when fitted thereto.

The handling device further includes a plug 35 slidably mounted within the inner cylindrical wall 22 of the carrier 20. The rear end of the plug is provided with  
5 a shoulder engageable with an internal step formed in the bore of the inner cylindrical wall 22, thereby to limit outward movement of the plug, from the carrier. The plug 35 has an enlarged head 36, which, in its normal position shown in Figures 1A and 1B, rests against the further wall 23 of the carrier. When in this position, a conical bore formed in the rear end of the plug locates around the  
10 forward end of the inner tube 33, also being a part of the carrier 20. An internal wall 37 separates the conical bore from the forward part of the plug. The plug 35 is a light frictional fit within the inner cylindrical wall 22 so that it will move with respect thereto only when positively pushed by an external force.

Figures 1A and 1B show the handling device 10 ready for use with the  
15 injector 12, to which a needle has already been attached by threading its hub 15 to the boss 13 of the injector, the sheath 17 remaining on the needle during this action to protect a user from accidental contact with the needle and also possible injury. In this condition, the injector has been pre-loaded with the medicament to be injected.

20 To commence an injection procedure, the handling device 10 is fitted to the forward end of the injector, simply by being pushed thereon. The cylindrical body 12 of the injector locates within the cylindrical sleeve 24 and the bushing 25 is pushed on to the outer surface of the needle hub 15, by the interaction of the rear



end of the cylindrical wall 22 of the carrier, with the forward end of the bushing 25. Further, the inner tube 23 is driven on to the sheath 17 protecting the needle. In view of the length of the sheath, part-way through fitting the handling device to the injector, the front end of the sheath contacts the internal wall 37 of the plug 35. In  
5 view of rigid character of the sheath, completing the fitting of the handling device to the injector drives the plug forwardly, partially out of the carrier as shown in Figure 1C.

Following the complete fitting of the handling device on the injector, the carrier 20 is gripped and pulled away from the injector, as shown in Figure 1D.  
10 This action removes the sheath 17 from the needle but leaves the cylindrical sleeve 24 on the injector, held in place by the bushing 25 engaged with the outer surface of the needle hub 15. The spring 29 maintains the sleeve 24 in its fully forward position, with the internal rib 28 thereof engaged with the rear end of the bushing 25. The injector is now ready to perform an injection.

15 Also as shown in Figure 1D, the presence of the plug projecting from the carrier 20 indicates to a user that the needle is unsheathed, and so is ready for use. Further, as the carrier is restrained for generally axial movement by the sleeve 24 located on the injector, the sheath is removed axially with respect to the needle and so will not contact that needle. In this way, damage to the sharp tip of  
20 the needle is avoided.

An injection is performed by presenting the forward end of the cylindrical sleeve 22 to an injection site, typically with the injector generally perpendicular to the skin. The injector is then pushed forwardly to achieve penetration by the

needle, the sleeve 24 retreating by sliding along the injector body against the action of spring 29, as shown in Figure 1E. The plunger of the injector may then be depressed to dispense the required dose of the medicament, through the needle 14 into the patient at the injection site. Both actions may be completed  
5 essentially continuously, by gripping the sleeve 24 and pressing the plunger, firstly to achieve needle penetration and then to complete the injection.

Following completion of the injection, the injector is withdrawn from the injection site, the sleeve 24 moving forwardly during this under the action of the spring 29 until the injector condition shown in Figure 1D is achieved once more.  
10 Then, the carrier 20 is picked up and is again pressed onto the forward end of the injector, so re-sheathing the needle. This is essentially the same condition as is shown in Figure 1C, except that an injection has been performed. Again, the carrier is moved axially by virtue of the presence of the cylindrical sleeve 24 on the injector and so re-sheathing of the needle may be achieved without risk of the  
15 needle engaging the internal wall of the sheath or possibly even penetrating the wall of the sheath.

In the position of Figure 1F, the sheath is still gripped by the inner tube 23 and the outer surface of the needle hub 15 remains engaged with the bore of the bushing 25, gripped thereby. The handling device 10 is removed from the injector  
20 by rotating the carrier 20 in an unscrewing sense (that is, counter-clockwise when viewed from the forward end of the injector) so unthreading the needle hub 15 from the threaded boss 13 of the injector. The needle hub eventually comes free of the

injector so that the entire handling device together with the needle located therewithin may be moved away from the injector (Figure 1F).

The procedure is completed by pressing the plug 35 back into the carrier 20, so ejecting the sheathed needle therefrom (Figure 1G). To perform this, the carrier  
5 could simply be held in one hand and the plug pushed in with a finger of the other hand, the carrier being held over a suitable receptacle for used needles such as a sharps container. Alternatively, the carrier could be stood on a suitable surface such as a desktop with the plug uppermost, whereafter the plug is pressed downwardly so freeing the needle from the carrier. As the needle is sheathed,  
10 there is no more risk attaching to this than when a fresh needle is mounted on the forward end of the injector.

Figures 2A to 2H shown a second embodiment of this invention, expressly adapted for use with a pen type of injector intended for the self-administration of medicaments. Insofar as there are components common with those described  
15 above with reference to the first embodiment, those components will be given like reference characters and will not be described again here.

The pen injector 40 is essentially conventional and so will not be described in detail. Briefly, the injector includes a cylindrical body 41 within which may be mounted a vial of the medicament to be self-administered, the forward end of that  
20 body having a threaded boss 13 to which may be secured a needle 14 having an internally-threaded hub 15. The rear end of the injector includes a mechanism 42 allowing the pre-selection of a dose of medicament and then, on depressing a plunger 43, the pre-set dose is dispensed out of an attached needle 14. Such

mechanisms are well-known and form no part of the present invention. A removable cap 44 is provided for the mechanism 42.

The handling device 46 of this second embodiment is functionally identical to that of the first embodiment but differs in that it is provided with a carrier 47 and  
5 a cylindrical sleeve 48 both having significantly greater axial lengths than the corresponding components of the first embodiment, such that the greater part of the cylindrical body 41 of the pen injector 40 is contained within the sleeve 48, when the handling device is fitted to the injector. Figures 2A and 2B show the handling device 46 fitted to the injector with the cap 44 in place, this being the  
10 normal storage condition for the injector. The rear end portion of the cylindrical sleeve is provided with a skirt 49 with which the forward end of the cap 44 engages, so wholly containing the pen injector. No needle is fitted to the injector and the plug 35 is in its rearmost position, within the handling device.

To prepare the injector for the self-administration of an injection, the cap 44  
15 is removed (Figure 2C) and then the handling device 46 is pulled away from the injector (Figure 2D). An entirely conventional self-injection sheathed needle assembly 50 is then threaded on to the boss 13 at the forward end of the injector body 41 (Figure 2E), whereafter the handling device 46 is pushed on to the injector body (Figure 2F), so causing the plug 35 to project forwardly from the handling  
20 device, as has been described above with reference to Figure 1C.

With the bushing 25 now engaged with the needle hub 15, the sleeve 48 is held to the injector body; on pulling the carrier 47 axially away therefrom (Figure 2G), the sleeve 48 remains on the injector, in its fully forward position urged by

spring 29. Following this, the required dose is pre-set on the mechanism 42 at the rear end of the injector, so that the injector is ready for performing an injection.

The injection, is performed by grasping the sleeve 48 in the fist of a user, typically with the thumb over the plunger 43, such that the plunger may be depressed thereby. The forward end of the sleeve 48 is presented to the injection site, and then the thumb is used to depress the plunger 43 with respect to the sleeve 48, which is held stationary by the operator. This initially causes the injector 40 to move forwardly within the sleeve 48 against the action of spring 29, so achieving needle penetration at the injection site. By maintaining the pressure on the plunger, when the injector has moved fully forwardly (Figure 2F) the dispensing mechanism of the plunger is activated, so driving the required dose out of the needle 14, into the injection site. Thus, only one simple action is required by the user, to achieve both needle penetration and dispensing of the medicament, which may be contrasted with the conventional procedure using a pen injector, where the two actions are performed quite separately.

On withdrawing the injector from the injection site, the injector 40 moves rearwardly with respect to the sleeve 48 (Figure 2G) and then the carrier 47 may once more be fitted to the sleeve (Figure 2H). The overall procedure may now be completed in one of two ways. In the first, the carrier 47 may be gripped and the plunger 35 pushed inwardly, so ejecting from the holding device the injector with the sheathed needle attached, whereafter the needle may be unscrewed from the injector and disposed of, as is currently performed with pen injectors. In the alternative, the carrier may be unscrewed in the same manner as has been

described above with reference to the first embodiment, such that the handling device 46 comes away from the injector with the sheathed needle still within that device. Thereafter, the carrier may be gripped and the plug pushed inwardly, to eject the sheathed needle from the handling device.

5           With both embodiments of this invention, there are the advantages of:

- Greatly enhanced operator safety, with no risk of accidental injury unlike the use of a conventional injector, were an attempt made to re-sheath the needle following the performance of an injection.
- Safety for all people in any way involved in the procedure, since the  
10           needle remains sheathed whenever detached from the injector.
- An injection may be performed with a single continuous action, rather than having separately to perform a first step of achieving needle penetration and then a second step of dispensing of the medicament.
- The sleeve makes it easier to achieve true axial penetration for the  
15           needle, so reducing the risk of pain to a patient.
- The needle is unsheathed without there being risk of the sheath contacting, and so damaging, the sharp tip of the needle.
- The needle itself is at all times concealed from the patient, either by  
20           the sheath or by the cylindrical sleeve once the handling device has been fitted to the injector, so reducing distress to a patient suffering needle aversion.

## CLAIMS

1. A handling device for use with a medical injector having a cylindrical body provided with a boss at the forward end thereof supporting a forwardly-projecting needle furnished with a protective sheath, which device comprises:

– a carrier having an outer cylindrical wall and co-axial therewith an inner tube  
5 which is a close sliding fit over the protective sheath of a needle;

– a cylindrical sleeve slidably mounted within the outer cylindrical wall of the carrier, the rear end of the sleeve being adapted to receive the cylindrical body of the injector;

– a bushing slidably located within the cylindrical sleeve, which bushing is  
10 retained within the sleeve and defines a bore for receiving the boss at the forward end of the injector body;

– spring means urging the bushing towards the rear end of the sleeve; and

– a plug slidably mounted on the carrier and projectable from the forward end thereof, the forward end of the sheath of a received injector engaging the plug;

15 whereby in use the device may be fitted to the forward end of an injector by receiving the injector cylindrical body in the sleeve and the boss in the bore of the bushing, the sheath then coupling to the inner tube of the carrier and the forward end of the sheath engaging the plug and pushing the plug forwardly with respect to the carrier to project therefrom, and on subsequent withdrawal of the carrier from  
20 the injector, the bushing and sleeve remain on the injector and the sheath remains within the carrier with the plug projecting from the forward end thereof.

2. A handling device as claimed in claim 1, wherein the carrier has an inner cylindrical wall connected at the forward end of the carrier to the outer cylindrical wall, the inner tube being connected to the rear end of the inner cylindrical wall.

3. A handling device as claimed in claim 2, wherein the cylindrical sleeve is  
5 slidable within the annular space between the inner and outer cylindrical walls of the carrier.

4. A handling device as claimed in claim 2 or claim 3, wherein the plug is slidably supported within the inner cylindrical wall of the carrier.

5. A handling device as claimed in claim 4, wherein the plug is a sufficient light  
10 frictional fit within said cylindrical wall to restrain movement of the plug with respect to the carrier under the influence of gravity.

6. A handling device as claimed in claim 4 or claim 5, wherein the length of the plug is such that the plug may be substantially wholly accommodated within the carrier prior to use of the device with an injector.

15 7. A handling device as claimed in any of claims 4 to 6, wherein the plug and the forward end of the inner cylindrical wall co-operate to limit forward movement of the plug, out of the carrier.

8. A handling device as claimed in any of the preceding claims, wherein the plug has an enlarged head at its forward end which lies externally of the carrier.

20 9. A handling device as claimed in any of the preceding claims, wherein the rear end of the sleeve is internally profiled to permit the bushing to be pushed into the sleeve thereafter to retain the bushing within the sleeve.



10. A handling device as claimed in claim 9, wherein the internal profile of the rear end of the sleeve includes one or more radially-inwardly directed nibs with which the bushing is engageable.

11. A handling device as claimed in any of the preceding claims, wherein the  
5 bushing includes an in-turned lip at the forward end thereof, which lip is engageable by the forward end of the injector boss to define an engaged relative position of the injector and the bushing.

12. A handling device as claimed in claim 11 when dependent on claim 2, wherein said lip of the bushing engages the rear end of the inner tube when the  
10 cylindrical sleeve is fully within the outer cylindrical wall of the carrier.

13. A handling device as claimed in any of the preceding claims, wherein the plug has a rearwardly-facing socket within which the forward end of the needle sheath of an injector is receivable.

14. A handling device as claimed in any of the preceding claims, wherein the  
15 spring means comprises a helical compression spring located within the sleeve and acting between the forward end of the sleeve and the bushing.

15. A handling device as claimed in any of the preceding claims, wherein the boss at the forward end of the cylindrical body is externally screw-threaded, for use with a needle having a hub with an internally-threaded socket co-operable with the  
20 threads of the boss.

16. A handling device as claimed in any of the preceding claims when dependent on claim 2, wherein the rear end of the plug locates in an annular space

between the inner cylindrical wall of the carrier and the inner tube, when the plug is fully within the carrier.

17. A handling device as claimed in any of the preceding claims, wherein the plug is of a contrasting colour to that of the carrier.

5 18. A handling device as claimed in any of the preceding claims, wherein the sleeve defines an elongate internal cavity of a sufficient length to accommodate the body of a pen-style injector intended for self administration, leaving only the plunger of the injector accessible.

19. A handling device as claimed in claim 1 and substantially as hereinbefore  
10 described, with reference to and as illustrated in the accompanying drawings.

20. The combination of a handling device as claimed in any one of the preceding claims and a medical injector having a cylindrical body provided with a boss at the forward end thereof for supporting a forwardly-projecting needle furnished with a protective a sheath, wherein the boss is receivable in the bore of  
15 the bushing, the sleeve is slidable rearwardly over the cylindrical body of the injector, and the sheath is connectable to the inner tube of the carrier.

21. A method of using a handling device as claimed in any one of claims 1 to 19 with a medical injector having a cylindrical body provided with an externally threaded boss at the forward end thereof for supporting a needle having an  
20 internally threaded hub engageable with the threads of the boss and a needle sheath surrounding and protecting the needle, comprising the steps of:

– threading the hub of a needle on to the boss of the injector;

– pushing the carrier on to the forward end of the injector so that the injector body is slidably received in the cylindrical sleeve, the boss carrying the needle hub is received in the bore of the bushing, the sheath is coupled to the inner tube, and the sheath engages the plug and pushes the plug forwardly to project from the  
5 carrier;





– pulling the carrier away from the cylindrical body of the injector with the sheath retained within the inner tube, the sleeve remaining on the injector body and the bushing remaining on the needle hub and boss, with the sleeve being urged forwardly by the spring to protect the needle;

10 and following the performance of an injection, during which the sleeve slides rearwardly over the injector body against the action of the spring to expose the needle as required:




– pushing the carrier once more on to the forward end of the injector so receiving the sleeve into the carrier and refitting the sheath on to the needle;

15 – rotating the carrier to unthread the needle hub from the boss and freeing the carrier from the injector body with the needle and sheath carried therewithin; and


– pressing the projecting plug back into the carrier, so driving the sheathed needle out of the handling device.











3/6





Fig 1a.





4/16

FIG 2A




FIG 2B




FIG 2c






FIG 2 D






FIG 2 E




FIG 2 F



6/6

